



## Features

- 7.5m power lead
- Current overload protection
- Hose-reel - optional extra
- 10m steel braided high pressure hose
- Starlet trigger gun safety cut-out and spray lance
- Includes chemical injection
- Total-Stop facility with delayed motor cut-out
- Continuously adjustable pressure and temperature control
- Brass pump head
- Ceramic-coated pump plungers
- Dry-run safety
- Diesel low level cut-out
- 4-way safety system with overload protection
- Water flow monitoring
- Safety thermostat

## Technical Specifications

## Kränzle Therm 1017 / 715



| Details                      | 1017         | 715          |
|------------------------------|--------------|--------------|
| Operating pressure           | 30 - 150 bar | 30 - 130 bar |
| Max. admissible overpressure | 170 bar      | 150 bar      |
| Water output                 | 16.7 l/min   | 11.6 l/min   |
| Nozzle size (flat jet)       | 40006        | 25045        |
| Heating output               | 68kW         | 55kW         |
| Hose drum                    | Additional   | Additional   |
| Connected load - 50Hz        | 400V, 8.5 A  | 230V, 15 A   |
| Motor speed                  | 1 400 r.p.m  | 1 400 r.p.m  |
| Motor rating                 | 5.5kW        | 3.4kW        |
| Weight with hose reel        | 212 kg       | 200 kg       |

*Specialist equipment for professional application*