



STEAM
VAPORE

STEAM GENERATOR

Industrial Bacchus

11^{kW} - 14,6^{kW} - 21,8^{kW} - 29^{kW} - 36,2

Steam generator

Boiler	Stainless steel AISI 304 with interchangeable heating element					
Body	Stainless steel AISI 304 BA					
Power supply	V - Hz	3~400 - 50/60				
Boiler output	kW/h	10,8	14,4	21,6	28,8	36
Maximum output	kW/h	11	14,6	21,8	29	36,2
Boiler volume	l	11		12	13	
Operating pressure	bar	6				
Water tank	l	20				
Steam production	g/min	291	388	582	776	970
	Kg/h	17,5	23	35	46,5	58
Steam T°	° C	165				
Weight	Kg	96				
Cable	m	8				
Dimensions (H x W x D)	cm	110 x 55 x 80				



BACCHUS

To be used with | da utilizzare con:



GEYSER 1
69



JULY
69



BACCHUS HOSE
67

FEATURES / CARATTERISTICHE



UNLIMITED
STEAM AUTONOMY



WATER MAINS
CONNECTION



WATER
TANK



AUTOMATIC
WATER REFILLING



POWER SWITCH
REGULATION



ELECTRIC
CONSOLE



BOILER CLEANING
SIGNAL

Bacchus Industrial is a steam generator with stainless-steel body and boiler, able to deliver dry saturated steam at 165°C. On board there is an electronic control console for the management of all generator functions.

Bacchus Industrial è un generatore ad uso professionale con scocca e caldaia in acciaio inox, in grado di sviluppare vapore saturo secco a 165°C. A bordo è presente una console elettronica di comando per la gestione e il controllo di tutte le funzioni del generatore.



To sanitize a bottling line from 700 to 3000 bottles/hour*

Sanificazione delle linee di imbottigliamento da 700 a 3000 bottiglie/ora*



To sanitize from 21 to 50 barrels per day*

Può sanificare da 21 a 50 barrique al giorno*

* approx. data/dati indicativi